Product data sheet
Characteristics

P7GB
APC Power-Saving Essential SurgeArrest, 7 Outlets, 120V

Purchase

Purchase	P7GB

Overview

Model Name	APC Power-Saving Essential SurgeArrest, 7 Outlets, 120V
Includes	User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Anguilla,Aruba,Bahamas,Barbados,Belize,Bermuda,Brazil,Canada,Colombia,Costa Rica,Cuba,Dominican Republic,Ecuador,El Salvador,Guatemala,Guyana,Haiti,Honduras,Jamaica,Mexico,Netherlands Antilles,Nicaragua,Panama,Puerto Rico,Trinidad And Tobago,Turks And Caicos Islands,United States,Venezuela,VIRGIN ISLANDS (UNITED STATES)

Output

Number of Outlets	7
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz
Input Connections	NEMA 5-15P
Cord Length	1.22 meters
Maximum Input Current	15

Surge Protection and Filtering

Surge energy rating	1080
Peak Current Common Mode	72
NM Surge Response Time (ns)	1
Let Through Voltage Rating	< 400

Physical

Net Weight	0.45 kg
Maximum Height	387 mm
Maximum Width	71 mm
Maximum Depth	36 mm
Shipping Weight	0.8 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Shipping Height	489 mm
Shipping Width	178 mm
Shipping Depth	41 mm
Master Carton Units	6.0
Master Carton Dimensions (Length x Width x Height)	352 mm x 263 mm x 541 mm
Master Carton Weight	6.15 kg
SCC Codes	1073130426924 0
Color	White
Units per Pallet	198.0

Environmental

Operating Environment	0 - 45 °C
Operating Relative Humidity	0 - 95
Operating Elevation	0-3000 meters
Storage Temperature	-5 - 45 °C
Storage Relative Humidity	0 - 95
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	ETL,UL 1449
Standard Warranty	Lifetime
Equipment protection policy	Lifetime : $50000
UL 1449 TVSS Rating	<400V

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs